

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/077499 A1

(51) International Patent Classification⁷: **B01D 65/10**

(21) International Application Number:
PCT/AU2005/000215

(22) International Filing Date: 18 February 2005 (18.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004900821 18 February 2004 (18.02.2004) AU

(71) Applicant (for all designated States except US): U.S.
FILTER WASTEWATER GROUP, INC. [US/US]; 181
Thorn Hill Road, Warrendale, PA 15086 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BECK, Thomas,
William [AU/AU]; 121 Keda Circuit, North Rich-
mond, NSW 2756 (AU). JOHNSON, Warren, Thomas
[AU/AU]; 87 Avoca Road, Grose Wold, NSW 2735 (AU).

(74) Agent: SHELSTON IP; 60 Margaret Street, Sydney,
NSW 2000 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: THE CONTINUOUS PRESSURE DECAY TEST

(57) Abstract: A continuous integrity test is performed on membranes in a membrane filtration system during the backwashing phase. The membrane pores are backwashed by applying a gas at a pressure below the bubble point to liquid permeate within the membrane lumens to displace the liquid permeate within the lumens through the membrane pores. An integrity test is performed on the membranes by allowing the gas pressure on the lumen side of the membrane walls to increase to a predetermined level above the pressure on the other side of the membrane walls, then isolating the lumen side of the membranes and measuring the reduction in gas pressure on the lumen side of the membrane walls resulting from gas passing through the membrane walls over a predetermined period. The measured reduction in pressure is then compared against a predetermined value to determine the integrity of said membranes.